



Lower Columbia Region Harbor Safety Committee

# **Columbia River Anchorage Guidelines**



## Table of Contents

<b>A. COLUMBIA RIVER ANCHORAGE GUIDELINES</b> .....	<b>3</b>
1. PURPOSE .....	3
2. SCOPE .....	3
3. AUTHORITY .....	3
4. DEVIATIONS FROM GUIDELINES .....	4
5. LENGTH OF VESSEL STAY .....	4
6. DEFINITIONS .....	4
7. ANCHORAGE NAMES .....	5
8. REFERENCES .....	5
<b>B. GENERAL GUIDELINES FOR ALL ANCHORAGES</b> .....	<b>6</b>
1. ANCHORING PROCEDURES.....	6
2. RESPONSE TO CHANGING CONDITIONS .....	7
3. GENERAL ANCHORAGE HAZARDS.....	7
<b>C. ADDITIONAL GUIDELINES FOR SPECIFIC ANCHORAGES</b> .....	<b>8</b>
1. ASTORIA NORTH ANCHORAGE .....	9
2. ASTORIA SOUTH ANCHORAGE .....	11
3. LONGVIEW ANCHORAGE .....	13
4. COTTONWOOD ISLAND ANCHORAGE .....	15
5. KALAMA ANCHORAGE .....	17
6. WOODLAND ANCHORAGE.....	19
7. HENRICI BAR ANCHORAGE.....	21
8. VANCOUVER LOWER ANCHORAGE .....	23
9. KELLEY POINT ANCHORAGE .....	25
10. VANCOUVER UPPER ANCHORAGE .....	27
<b>D. OFFSHORE ANCHORING</b> .....	<b>29</b>
1. CAUTION.....	29
2. EMERGENCY OFFSHORE ANCHORING REQUIREMENTS .....	29



## A. Columbia River Anchorage Guidelines

### 1. Purpose

The Columbia River Anchorage Guidelines are intended to raise awareness of and mitigate hazards common to anchoring in the Columbia River System. Common hazards include (but are not limited to):

- Traffic,
- Local Weather Patterns,
- Changing River Volumes,
- Tides,
- Currents,
- Fishing Activities,
- Recreational River Usage, and
- Lack of immediate availability of Tug and Launch Services.

River conditions constantly change. Masters, Pilots and Agents must take all current and impending circumstances into account a) when anchoring vessels and b) while vessels are at anchor in order to avoid swinging into the channel, collisions, allisions and groundings.

The Columbia River Anchorage Guidelines:

- Were cooperatively drafted by regulators and industry representatives and provide information unique to the river system and its anchorages that may be required in order to anchor safely.
- Are to be implemented in accordance with all International, Federal, State and Local regulations, and the normal practices of good seamanship.
- Constitute the Minimum Standards of Care to be used in all anchoring operations on the Columbia River System.

### 2. Scope

The Columbia River Anchorage Guidelines apply to the use of all **Designated** and **Non-Designated Anchorages** in the Columbia River System.

### 3. Authority

The U. S. Coast Guard is authorized under the Ports and Waterways Safety Act (33 CFR § 109.07) to direct the anchoring of vessels. Individual Masters and Pilots will anchor vessels in a safe position for their size, draft and duration at anchor. Pilots are available on short notice to reposition ships that may have worked out of position. Vessel Masters shall immediately contact a Pilot for repositioning their vessel when required.



#### 4. Deviations from Guidelines

The Master or Pilot (in consultation with the Captain of the Port) may deviate from these guidelines when an alternate approach will provide an equivalent or higher level of safety. Vessel Masters shall inform the **U.S. Coast Guard Sector Portland 503-240-9311** and the appropriate Pilot organization (**Columbia River Pilots 503-289-9922** or the **Columbia River Bar Pilots 503-325-2641**), when such deviations are anticipated or have occurred.

#### 5. Length of Vessel Stay

In accordance with 33 CFR 110.228(b) (3) no vessel may occupy a designated anchorage for more than 30 consecutive days without a permit from the Captain of the Port. Vessels remaining at a designated anchorage for more than seven days may be contacted by the US Coast Guard to obtain an update on the vessels' operational status.

#### 6. Definitions

- **Bunkering** is the transfer of fuel.
- **Bankfull Stage** is a given stage determined by the U.S. Army Corps of Engineers and used to schedule releases from reservoirs. Normally, Bankfull Stage is below Flood Stage.
- **Columbia River Datum (CRD)** is the plane of reference from which river stage is measured on the Columbia River from the lower Columbia River up to Bonneville Dam, and on the Willamette River up to Willamette Falls. Equals 1.82 feet above **Mean Sea Level** (equivalent to NGVD) at Vancouver, Washington.
- **Common Names** are names in common use locally that do not coincide with the names listed in 33 CFR 110.228.
- **Designated Anchorages** are those anchorages listed in 33 CFR 110.228.
- **Lightering** is the transfer of cargo in bulk from one vessel to another vessel while at anchor.
- **Non-Designated Anchorages** are other viable anchorages that are not designated in 33 CFR 110.228.
- **River Mile** is the distance in statute miles beginning at the mouth of the Columbia River. Tables for converting statute miles to nautical miles are contained in Coast Pilot 7.
- **Mean Lower Low Water (MLLW)** tidal datum is the average of the lower low water height of each tidal day observed over the National Tidal Datum Epoch. For stations with shorter series, simultaneous observational comparisons are made with a control tide station in order to derive the equivalent datum of the National Tidal Datum Epoch.



## 7. Anchorage Names

The following table lists the **CFR Designated Name** and **Common Name** for each **Designated Anchorage**.

<b>Designated Anchorage</b> (As listed in the CFR)	<b>Common Name</b>	<b>Common Names of anchorages adjacent to or included in other anchorages</b>
1. <b>Astoria North Anchorage</b>	North Anchorage	<ul style="list-style-type: none"> <li>• Between Buoys 37 and 39</li> <li>• Above Buoy 39</li> <li>• The Hole (below Buoy 43)</li> </ul>
2. <b>Astoria South Anchorage</b>	South Anchorage	<ul style="list-style-type: none"> <li>• Below Buoy 40</li> <li>• Between Buoys 40 and 42</li> <li>• Above Buoy 42</li> </ul>
3. <b>Longview Anchorage</b>	Longview Anchorage	<ul style="list-style-type: none"> <li>• TBN</li> </ul>
4. <b>Cottonwood Island Anchorage</b>	Cottonwood Island Anchorage	<ul style="list-style-type: none"> <li>• Rainier Anchorage</li> <li>• Below Buoy 36</li> <li>• Above Buoy 36</li> </ul>
5. <b>Kalama Anchorage</b>	Kalama Hole	<ul style="list-style-type: none"> <li>• Kalama Anchorage</li> <li>• Turning Basin (Hole)</li> <li>• Sandy Island</li> </ul>
6. <b>Woodland Anchorage</b>	Woodland Anchorage	<ul style="list-style-type: none"> <li>• Columbia City Anchorage</li> </ul>
7. <b>Henrici Bar Anchorage</b>	Henrici Bar Anchorage	<ul style="list-style-type: none"> <li>• Fish Trap</li> <li>• Willow Point</li> </ul>
8. <b>Lower Vancouver Anchorage</b>	Lower Vancouver Anchorage	<ul style="list-style-type: none"> <li>• Morgan's (Above Pipeline)</li> <li>• Hewlitt Point (Below Pipeline)</li> <li>• Caterpillar Island</li> <li>• Reeder's</li> </ul>
9. <b>Kelley Point Anchorage</b>	Upper Vancouver Anchorage	<ul style="list-style-type: none"> <li>• Kelly Point Hole</li> </ul>
10. <b>Upper Vancouver Anchorage</b>	Upper Vancouver Anchorage	<ul style="list-style-type: none"> <li>• Lower Buoy</li> <li>• Below Upper Buoy</li> <li>• Upper Buoy</li> <li>• Below Power Line</li> <li>• Power Line</li> <li>• Above Power Line</li> </ul>

## 8. References

USCG Authority 33 Code of Federal Regulation (CFR), Part 109, Ports and Waterways Safety Act, 33 CFR 110.228; 33 USC 1221 et seq; 33 USC 471; 49 USC 1655 (g)(1); 49 CFR 1.46 ((c)(1)); Inland Rules of the Road.



## **B. General Guidelines for All Anchorages**

### **1. Anchoring Procedures**

The vessel Master and crew shall:

#### ***Prior to Anchoring:***

- a. Review the General and Specific Guidelines in this document and the Coast Pilot concerning your anchorage.
- b. Confer with your Pilot to ascertain expected condition changes while at anchor.
- c. Establish a Point of Contact to order tug assistance.
- d. Establish and document the lead time for tug arrival with the Point of Contact.
- e. Have a gangway rigged and ready for use.
- f. Clear **anchors** for letting go. All classed foreign and domestic vessels subject to Title 33 Code of Federal Regulation (CFR), Part 164 transiting the Columbia River, shall have the required number of operational anchors as designated for that class of vessel.

**Master's Orders** to include orders to keep Engines on Standby:

- a. During conditions of forecast high winds,
- b. In crowded anchorages during tidal changes, and
- c. In anchorages with poor holding ground.
- d. Call the Master and Duty Engineer immediately should the anchor start to drag.

#### ***While at Anchor:***

Maintain a proper Deck Watch at all times. Deck Watch personnel shall:

- a. Check the condition of the anchors and anchor gear while making periodic rounds of the vessel.
- b. Continuously monitor the vessels position as well as other vessels, paying particular attention to potential of dragging anchor or swinging toward a hazard.
- c. Monitor VHF channels 16 and 13 at all times.
- d. Confirm vessel's position and under keel clearance at a minimum of once per hour, more frequently if weather conditions deteriorate.
- e. Monitor weather forecasts on a regular basis.
- f. Call the Master and Duty Engineer immediately if the anchor is dragging.

Maintain a proper Engine Room Watch at all times. Engine Watch personnel shall remain ready to answer all bells in the event of dragging or losing an anchor.



## 2. Response to Changing Conditions

### During Periods of Restricted Visibility

All of the above plus:

- a. Maintain Bridge Watch with Licensed Deck Officer.
- b. Maintain Traffic Watch on Radar.

### When Gale Warnings are in Effect (Sustained Winds of 28 – 47 Knots)

All of the above plus:

- a. The Bridge Watch must be maintained by a Licensed Deck Officer.
- b. Engines on Standby, ready to provide immediate propulsion.

### When Storm Warnings are in Effect (Sustained Winds exceed 48 knots)

All of the above plus:

- a. Consider increasing the scope of anchor chain.
- b. Determine the availability and locations of potential stand by tugs (with appropriate size and horsepower), which could assist the vessel in holding position.
- c. Assess the need to have tugs alongside.
- d. Assess the need for a Pilot and get one onboard if necessary.

## 3. General Anchorage Hazards

### Low Water

Low Water occurs when the River Stage is about 5 feet above the Columbia River Datum (CRD) and can be expected to occur between the months of September and November.

During periods of Low Water adequate consideration shall be given to:

- Under keel clearance to avoid the increased possibility of grounding.
- Tidal currents may begin to flow upriver during on flood tides.
- Vessels are more likely to swing at anchor.
- If vessels drag anchor, they may ground, block the channel, or alide with other objects.



When anchoring during periods of Low Water, Pilots and Masters should evaluate the following factors:

- The size of the vessel compared to the characteristics of the anchorage.
- Reduction of the scope of the anchor to the minimum necessary to safely hold the vessel.
- The anticipated length of stay in anchorage with regard to tide cycles.
- Anticipated operations while at anchor and their impact on the ability of the vessel to get underway.
- The amount of anchor chain that the vessel carries.
- The size of other vessels in the anchorage (and in particular, large vessels).
- Proximity of other vessels within the anchorage.
- Anticipated under keel clearance.
- Potential for grounding or dragging anchor.

### **High Water**

High Water occurs when the River Stage is about 10 feet above CRD and can be expected to occur between the months of January and June.

During periods of High Water adequate consideration shall be given to:

- The higher potential of dragging anchor because of high water flows.
- Anchor chains may be fouled by floating debris.
- The current in the anchorage may exceed 5 knots or more.
- When high water conditions approach the Bankfull Stage (maximum safe water level which will not overflow the river banks) other moorings may become submerged resulting in more demand for anchorages.

### **C. Additional Guidelines for Specific Anchorages**

The Additional Guidelines provide locally generated information (in addition to that provided in 33 CFR 110.228 (a) (1) and other published authorities). The prudent mariner should study all generally available information and then supplement that information with the information contained in this guideline.



## 1. Astoria North Anchorage

### Common Local Alternative Name

Anchorage positions are referred to according to their proximity to the closest buoy. “The Hole” refers to the deep anchorage position just west of Buoy 43.

### Location

Between River Miles 14.0 and 17.8

- US Chart # 18521
- BA Chart # 2839
- 33 CFR 110.228 (a) (1)
- Coast Pilot 7 Chapter 2

### Anchorage Depth(s)

Depths range from 24’ (7.32M) to over 45’ (13.72M) MLLW. Deeper anchorages are to the east. All vessels are encouraged to arrive with drafts of 23’ (7M) or less to facilitate maximum use of anchorage grounds.

### Buoys

There are no anchorage buoys.

### Vessel Sizes

Normally this anchorage is limited to vessels under 740’ (225.55M) LOA.

### Anchorage Capacity

This anchorage approximately 2.5 miles long and is divided into anchorage spots approximately every ½ mile. Under normal conditions, there is room for six vessels to be anchored within this anchorage area; however “The Hole” just west of Buoy 43 is normally kept vacant for deep draft vessels in unusual situations or emergencies or short term anchoring.

### Vessel Orientation at Anchor

Vessels normally stem the prevailing Columbia River current. On slack currents or when winds oppose the prevailing current vessels can swing in any direction.

### Grounding Potential

Normally the risk of grounding in this anchorage is low for the first few days. As the length of stay increases, a vessel’s anchor may walk out of position increasing the risk of grounding or blocking the channel.

### Bunkering and Lightering

Bunkering may occur in the Astoria North Anchorage. Lightering operations are limited to the transfer of the fish cargo of processing vessels.



### **Cargoes of Particular Hazard**

Vessels carrying a Cargo of Particular Hazard as listed in 33 CFR 126.10 may not occupy this anchorage.

### **Length of Vessel Stay**

Vessels normally remain at this anchorage for no more than seven days. They may be required to reposition their anchor after two days or move up river after seven days.

### **Special Considerations**

Additional considerations specific to the Astoria North Anchorage include:

- Limited space is available in this anchorage for the size of the vessels that typically anchor here; care must be taken to avoid crowding.
- Vessels over 740' (225.55M) may be anchored under special circumstances and may require a tug standing-by.
- When the anchorage is crowded ebb current may be required for anchoring.
- Anchoring in fog is not recommended in a crowded anchorage.
- Vessels over 28' (8.53M) draft should not be anchored in Astoria North Anchorage due to the probability of dragging anchor. A vessel with over 28' (8.53M) of draft may require tug(s) to standby.
- This anchorage should be vacated in anticipation of Hurricane Force winds.
- Ships can swing into the channel at the change of the tide. With ships in both Astoria North and South Anchorages they can swing towards each other and block the channel.
- Ships that stay three or more days should expect to be repositioned due to the tendency for the anchor to walk out of position.
- In this anchorage it is important to anticipate, to the degree possible, the effects of changes in wind, current, and water level, both upon the anchoring vessel and upon other nearby vessels.
- During the winter (usually between November and March), winds change direction and force at short notice with the passing of fronts. Anchored vessels must maintain a close watch on their position and be prepared to use their engines to prevent dragging into other ships or going aground and will swing on tidal changes.
- This anchorage should not be used for extended stays during the winter season.

### **Emergency Situations**

Tugs are not normally available on short notice but can be arranged with approximately six hours notice by contacting the vessel's agent or pilots on VHF channel 13. Pilots are normally available within an hour, but can arrive earlier in an emergency.



## 2. Astoria South Anchorage

### Common Local Alternative Name

Anchorage positions are referred to according to their proximity to the closest buoy.

### Location

Between River Miles 15.0 and 18.2

- US Chart # 18521
- BA Chart # 2839
- 33 CFR 110.228 (a) (2)
- Coast Pilot 7 Chapter 2

### Anchorage Depth(s)

Depths range from 20' (6.10M) to over 45' (13.73M) MLLW. Deeper anchorages are on either end.

### Buoys

There are no anchorage buoys.

### Vessel Sizes

Normally this anchorage is limited to vessels under 650' (198.12M) LOA. Positions on either end are only suitable for smaller vessels in good conditions.

### Anchorage Capacity

This anchorage approximately 2.75 miles long and is divided into anchorage spots approximately every ½ mile. Under normal conditions, there is room for four vessels to be anchored within this anchorage area.

### Vessel Orientation at Anchor

Vessels normally stem the prevailing Columbia River current. On slack currents or when winds oppose the prevailing current vessels can tend in any direction.

### Grounding Potential

Normally the risk of grounding in this anchorage is low for the first few days. As the length of stay increases, a vessel's anchor may walk out of position increasing the risk of grounding or blocking the channel.

### Bunkering and Lightering

Bunkering may occur in the Astoria South Anchorage. Lightering operations are limited to the transfer of the fish cargo of processing vessels.

### Cargoes of Particular Hazard

Vessels carrying a Cargo of Particular Hazard as listed in 33 CFR 126.10 may not occupy this anchorage.



## Length of Vessel Stay

This is a short term anchorage and stays are normally limited to less than two days.

## Special Considerations

Additional considerations specific to the Astoria South Anchorage include:

- Limited space is available in this anchorage for the size of the vessels that typically anchor here; care must be taken to avoid crowding.
- Vessels over 650' (198.12M) may be anchored under special circumstances and may require a tug standing-by.
- When the anchorage is crowded ebb current may be required for anchoring.
- Anchoring in fog is not recommended.
- Vessels over 26' (7.93M) draft should not be anchored in Astoria South Anchorage due to the probability of dragging anchor.
- This anchorage should be vacated in anticipation of Storm Force winds.
- Ships can swing into the channel at the change of the tide. With ships in both Astoria North and South Anchorages they can swing towards each other and block the channel.
- Ships that stay more than one day may have to be repositioned due to the tendency for the anchor to walk out of position.
- In this anchorage it is important to anticipate, to the degree possible, the effects of changes in wind, current, and water level, both upon the anchoring vessel and upon other nearby vessels.
- During the winter (usually between November and March), winds change direction and force at short notice with the passing of fronts. Anchored vessels must maintain a close watch on their position and be prepared to use their engines to prevent dragging into other ships or going aground and vessels will swing during tidal changes.
- This anchorage should not be used for extended stays during the winter season.

## Emergency Situations

Tugs are not normally available on short notice but can be arranged with approximately six hours notice by contacting the vessel's agent or pilots on VHF channel 13. Pilots are normally available within an hour, but can arrive earlier in an emergency.



### 3. Longview Anchorage

#### **Common Local Alternative Name**

Longview Anchorage

#### **Location**

Between River Miles 64.0 and 66.0

- US Chart # 18524
- BA Chart # 2849
- 33 CFR 110.228 (a) (3)
- Coast Pilot 7 Chapter 2

#### **Anchorage Depth(s)**

Depths range from 29' to 40' CRD.

#### **Buoys**

There are no anchorage buoys.

#### **Vessel Sizes**

Normally this anchorage is limited to vessels under 650' (198.17M) LOA.

#### **Anchorage Capacity**

This anchorage runs from Buoy 23 to the Longview Bridge (approximately 1.5 miles long) and can accommodate five vessels.

#### **Vessel Orientation at Anchor**

Vessels normally anchor facing upstream; in lower water conditions vessels will stem the tide. Vessels will stem the prevailing wind in slack water conditions.

#### **Grounding Potential**

Normally the risk of grounding in this anchorage is low.

#### **Bunkering and Lightering**

Bunkering may occur in the Longview Anchorage. Lightering operations are not allowed in this anchorage.

#### **Cargoes of Particular Hazard**

Vessels carrying a Cargo of Particular Hazard as listed in 33 CFR 126.10 may occupy this anchorage with permission from the Captain of the Port.

#### **Length of Vessel Stay**

Vessels normally remain at this anchorage for no more than seven days. After seven days vessels may be contacted by the USCG for status.



## Special Considerations

Additional considerations specific to the Longview Anchorage include:

- Vessels over 600' (182.93M) in length are better situated just above Buoy 23 because of more room to swing.
- Loaded ships should use caution as they tend to move toward channel while at anchor.
- Vessels greater than 650' (198.12M) in length may use the anchorage with a tug standing by.
- In this anchorage it is important to anticipate, to the degree possible, the effects of changes in wind, current, and water level, both upon the anchoring vessel and upon other nearby vessels, and barges.
- During seasonal periods of low water levels (usually between September and November) anchoring vessels must remain aware of their under keel clearance while at anchor and of the possibility of going aground and are more likely to swing on tidal changes.

## Emergency Situations

Tugs are normally not available on short notice and can require a three hour notice. They can be notified on channels 16, 13 or by contacting the vessel's agent.



## 4. Cottonwood Island Anchorage

### Common Local Alternative Name

Cottonwood Island Anchorage is a long anchorage and can be described as Above buoy #36, Below buoy #36, and Rainier Anchorage.

### Location

Between River Miles 66.7 and 71.2

- US Chart # 18524
- BA Chart # 2849
- 33 CFR 110.228 (a) (10)
- Coast Pilot 7 Chapter 2

### Anchorage Depth(s)

Depths range from 19' to over 40' CRD.

### Buoys

There are no anchorage buoys.

### Vessel Sizes

Normally this anchorage is limited to vessels under 650' (198.17M) LOA.

### Anchorage Capacity

This anchorage is 4.5 miles long. If vessels are anchored 0.25 miles apart, the anchorage can accommodate three vessels above buoy #36 and 10 vessels below buoy #36.

### Vessel Orientation at Anchor

Vessels normally anchor facing upstream; in lower water conditions vessels will stem the tide. Vessels will stem the prevailing wind in slack water conditions.

### Grounding Potential

Normally the risk of grounding in this anchorage is low.

### Bunkering and Lightering

Bunkering may occur in the Cottonwood Island Anchorage. Lightering operations are not allowed in this anchorage.

### Cargoes of Particular Hazard

Vessels carrying a Cargo of Particular Hazard as listed in 33 CFR 126.10 may occupy this anchorage with permission from the Captain of the Port.



### **Length of Vessel Stay**

Vessels normally remain at this anchorage for no more than seven days. After seven days vessels may be contacted by the USCG for status.

### **Special Considerations**

Additional considerations specific to the Cottonwood Island Anchorage include:

- Vessels over 600' (182.93M) in length are better situated above Cottonwood Island light 33, because there is more room to swing.
- Loaded ships should use caution as they tend to move toward the channel while at anchor.
- Vessels greater than 650' (198.12M) in length may use the anchorage with a tug standing by.
- Depths to over 40' CRD exist within the lower 1.5 miles of the anchorage off Rainier.
- In this anchorage it is important to anticipate, to the degree possible, the effects of changes in wind, current, and water level, both upon the anchoring vessel and upon other nearby vessels, and barges.
- During seasonal periods of low water levels (usually between September and November) anchoring vessels must remain aware of their under keel clearance while at anchor and of the possibility of going aground and are more likely to swing on tidal changes.

### **Emergency Situations**

Tugs are normally not available on short notice and can require a three hour notice. They can be notified on channels 16, 13 or by contacting the vessel's agent.



## 5. Kalama Anchorage

### Common Local Alternative Name

Kalama Anchor is the common name for the Kalama Turning Basin area (just above Coffin Rock). Sandy Island describes the upper portion of the anchorage.

### Location

Between River Miles 73.2 and 76.2

- US Chart # 18524
- BA Chart # 2849
- 33 CFR 110.228 (a) (4)
- Coast Pilot 7 Chapter 2

### Anchorage Depth(s)

Depths in the anchorage range from 26' (7.93M) to over 40' (12.19 M) CRD.

### Buoys

There are no anchorage buoys.

### Vessel Sizes

No length restrictions in the turning basin area. The area off Sandy Island will accommodate vessels under 600' (182.93 M).

### Anchorage Capacity

It is permissible to anchor one vessel in the turning basin area. A tug will be required to standby the vessel and not allow it to swing because of the close proximity to the channel. The area off Sandy Island is approximately 1.25 miles long and will accommodate six vessels.

### Vessel Orientation at Anchor

Vessels normally anchor facing upstream. In lower water conditions vessels will stem the tide. Vessels will stem the prevailing wind in slack water conditions.

### Grounding Potential

Normally the risk of grounding in this anchorage is low.

### Bunkering and Lightering

Bunkering may occur in the Kalama Anchorage. Lightering operations are not allowed in this anchorage.

### Cargoes of Particular Hazard

Vessels carrying a Cargo of Particular Hazard as listed in 33 CFR 126.10 may occupy this anchorage with permission from the Captain of the Port.



### **Length of Vessel Stay**

Vessels normally remain at this anchorage for no more than seven days. After seven days vessels may be contacted by the USCG for status.

### **Special Considerations**

Additional considerations specific to the Kalama Anchorage include:

- Vessels greater than 650' (198.12M) in length may use the anchorage with a tug standing by.
- In this anchorage it is important to anticipate, to the degree possible, the effects of changes in wind, current, and water level, both upon the anchoring vessel and upon other nearby vessels, and barges.
- During seasonal periods of low water levels (usually between September and November) anchoring vessels must remain aware of their under keel clearance while at anchor and of the possibility of going aground and are more likely to swing on tidal changes..

### **Emergency Situations**

Tugs are normally not available on short notice and can require a three hour notice. They can be notified on channels 16, 13 or by contacting the vessels agent.



## 6. Woodland Anchorage

### Common Local Alternative Name

Columbia City Anchorage

### Location

Between River Miles 83.6 and 84.3

- US Chart # 18524
- BA Chart # 2849
- 33 CFR 110.228 (a) (5)
- Coast Pilot 7 Chapter 2

### Anchorage Depth(s)

Depths range from 8' (2.44 M) to over 40' (12.19 M) Columbia River Datum (CRD).

### Buoys

There are no anchorage buoys.

### Vessel Sizes

Generally for vessels under 600' (182.93 M) in length.

### Anchorage Capacity

This is a small anchorage approximately 0.75 miles long. This anchorage will accommodate up to three vessels.

### Vessel Orientation at Anchor

Vessels normally anchor facing upstream. In lower water conditions vessels will stem the tide. Vessels will stem the prevailing wind in slack water conditions.

### Grounding Potential

Normally, the risk of grounding at this anchorage is low.

### Bunkering and Lightering

Bunkering may occur in the Woodland Anchorage. Lightering operations are not allowed in this anchorage.

### Cargoes of Particular Hazard

Vessels carrying a Cargo of Particular Hazard as listed in 33 CFR 126.10 may occupy this anchorage with permission from the Captain of the Port.

### Length of Vessel Stay

Vessels normally remain at this anchorage for no more than seven days. After seven days vessels may be contacted by the USCG for status.



## Special Considerations

Additional considerations specific to the Woodland Anchorage include:

- Columbia City is a remote anchorage and not currently used.
- Vessels greater than 600' (182.88M) in length may use the anchorage with a tug standing by.
- In this anchorage it is important to anticipate, to the degree possible, the effects of changes in wind, current, and water level.
- During seasonal periods of low water levels (usually between September and November) anchoring vessels must remain aware of their under keel clearance while at anchor and of the possibility of going aground and are more likely to swing on tidal changes.

## Emergency Situations

Tugs are normally not available on short notice and can require a three hour notice. They can be notified on channels 16, 13 or by contacting the vessels agent.



## 7. Henrici Bar Anchorage

### Common Local Alternative Name

Fish Trap, Willow Point (not Willow Bar)

### Location

Between River Miles 91.6 and 93.9

- US Chart # 18525
- BA Chart # 2849
- 33 CFR 110.228 (a) (6)
- Coast Pilot 7 Chapter 2

### Anchorage Depth(s)

Useable depths range from 22' (6.71 M) to over 33' (10.06 M) CRD.

### Buoys

There are no anchorage buoys.

### Vessel Sizes

Generally for vessels under 600' (182.93 M) in length.

### Anchorage Capacity

Henrici Bar Anchorage is a narrow anchorage about 2 miles long, and will accommodate up to eight vessels.

### Vessel Orientation at Anchor

Vessels normally anchor facing upstream. In lower water conditions vessels will stem the tide. Vessels will stem the prevailing wind in slack water conditions.

### Grounding Potential

Normally the risk of grounding in this anchorage is low.

### Bunkering and Lightering

Bunkering may occur in the Henrici Bar Anchorage. Lightering operations are not allowed in this anchorage.

### Cargoes of Particular Hazard

Vessels carrying a Cargo of Particular Hazard as listed in 33 CFR 126.10 may occupy this anchorage with permission from the Captain of the Port.

### Length of Vessel Stay

Vessels normally remain at this anchorage for no more than seven days. After seven days vessels may be contacted by the USCG for status.



### **Special Considerations**

Additional considerations specific to the Henrici Bar Anchorage include:

- This is a remote anchorage and not currently used.
- Vessels greater than 600' (182.88M) in length may use the anchorage with a tug standing by.
- In this anchorage it is important to anticipate, to the degree possible, the effects of changes in wind, current, and water level.
- During seasonal periods of low water levels (usually between September and November) anchoring vessels must remain aware of their under keel clearance while at anchor and of the possibility of going aground and are more likely to swing on tidal changes and are more likely to swing on tidal changes.

### **Emergency Situations**

Tugs are normally not available on short notice and can require a two hour notice. They can be notified on channels 16, 13 or by contacting the vessels agent.



## 8. Vancouver Lower Anchorage

### Common Local Alternative Name

Willow Bar Lower Anchorage

### Location

Between River Miles 96.2 and 101.0

- US Chart # 18525
- BA Chart # 2849
- 33 CFR 110.228 (a) (7)
- Coast Pilot 7 Chapter 2

### Anchorage Depth(s)

Depths range from 25' (7.62 M) to over 40' (12.19 M) CRD.

### Buoys

There are no anchorage buoys.

### Vessel Sizes

Normally this anchorage is limited to vessels under 600' (182.93M) LOA.

### Anchorage Capacity

This anchorage is approximately 4 miles long. Under normal conditions, up to fourteen vessels may be anchored within this anchorage area and are arrayed from upstream to downstream.

### Vessel Orientation at Anchor

Vessels normally anchor facing upstream, stemming the prevailing Columbia River current.

### Grounding Potential

Normally the risk of grounding in this anchorage is low.

### Bunkering and Lightering

Bunkering may occur in the Willow Bar anchorage; barge to barge petroleum lightering operations are allowed in this anchorage. Ship-to-ship and ship-to-barge lightering operations are not allowed in this anchorage.

### Cargoes of Particular Hazard

Vessels carrying a Cargo of Particular Hazard as listed in 33 CFR 126.10 may occupy this anchorage with permission from the Captain of the Port.

### Length of Vessel Stay

Vessels normally remain at this anchorage for no more than seven days. After seven days vessels may be contacted by the USCG for status.



## Special Considerations

Additional considerations specific to the Willow Bar Anchorage include:

- Limited space available in this anchorage and the size of the vessels that typically anchor here, care must be taken to avoid crowding.
- Vessels greater than 650' (198.12M) in length may use the anchorage with a tug standing by.
- Pipeline is located between River Mile 100.16 and 100.45. Vessels do not anchor in this area.
- A Rock Pile is located on Morgan Bar and lies in position Lat. 45° 41' 49.8823" N, Long. 122° 46' 06.0792" W (outside the designated anchorage boundaries). Minimum depth at the Rock Pile is 13' (3.96M) below CRD.
- Anchoring vessels and vessels in the anchorage should anticipate the effects of changes in wind, current, and water level, in order to avoid potential swinging into the channel or other vessels.
- During seasonal low water anchoring vessels must remain aware of a) their under keel clearance, b) the potential for grounding and c) the increased probability of swinging on tidal changes.
- The preferred location for barge-to-barge lightering operations is in the anchorage area abeam of Reeder Point Light 28 at the lower end of Caterpillar Island. A WDFW boat launch is located at the lower end of the slough behind Caterpillar Island.

## Emergency Situations

Tugs are normally available on short notice and can be notified on channels 16, 13 or by contacting the vessels agent.



## 9. Kelley Point Anchorage

### Common Local Alternative Name

Vancouver Upper Anchorage, Kelley Point Hole

### Locations

Kelley Point Anchorage

Between River Miles 101.6 and 102.0

Vancouver Upper Anchorage

Between River Miles 102.6 and 105.0

- US Chart # 18526
- BA Chart # 2849
- 33 CFR 110.228 (a) (8)
- Coast Pilot 7 Chapter 2

### Anchorage Depth(s)

Depth is a minimum of 50' (15.24M) CRD.

### Buoy

No buoys are available.

### Tugs

Vessels must be attended by a tug at all times.

### Vessel Sizes

The anchorage is open to vessels of any size.

### Anchorage Capacity

One vessel may be anchored within this anchorage.

### Vessel Orientation at Anchor

Vessels normally anchor facing upstream, stemming the prevailing Columbia River current.

### Grounding Potential

Normally the risk of grounding in this anchorage is low.

### Bunkering and Lightering

Bunkering may occur. Lightering operations are not allowed.

### Cargoes of Particular Hazard

Vessels carrying a Cargo of Particular Hazard as listed in 33 CFR 126.10 may occupy this anchorage with permission from the Captain of the Port.



### **Length of Vessel Stay**

This is a short stay anchorage. After seven days vessels may be contacted by the USCG for status.

### **Special Considerations**

Additional considerations specific to the Kelley Point Anchorage include:

- In this anchorage it is important to anticipate, to the degree possible, the effects of changes in wind, current, and water level, both upon the anchoring vessel and other nearby vessels, and barges.
- This is a high traffic area.

### **Emergency Situations**

Additional tugs are normally available on short notice and can be notified on channels 16, 13 or by contacting the vessels agent.



## 10. Vancouver Upper Anchorage

### Common Local Alternative Name

Hayden Island Upper Anchorage

### Location

Between River Miles 102.57 and 105.20

- US Chart # 18526
- BA Chart # 2849
- 33 CFR 110.228 (a) (9)
- Coast Pilot 7 Chapter 2

### Anchorage Depth(s)

Depths range from 35' (10.67M) to over 50' (15.24M) CRD.

### Buoys

Two stern buoys are located in the anchorage.

### Buoy Usage

Vessels over 650' (198.12M) LOA will use one of the two stern buoys if available. Under normal conditions, vessels 650' (198.12M) LOA or less may elect to anchor without using a stern buoy.

### Vessel Sizes

The anchorage is open to vessels of any size.

### Anchorage Capacity

Under normal conditions, up to seven vessels may be anchored within this anchorage area and is arrayed from west to east.

### Vessel Orientation at Anchor

Vessels normally anchor facing upstream, stemming the prevailing Columbia River current.

### Grounding Potential

Normally the risk of grounding in this anchorage is low. Deep draft anchorages are generally to the West. Vessels not using a stern buoy need to pay close attention to swinging while at anchor.

### Bunkering and Lightering

Bunkering may occur in any Hayden Island anchorage; ship-to-ship and ship-to-barge lightering operations are only allowed when a stern buoy is utilized. Barge-to-barge lightering operations are allowed above the power line crossing only and do not require a stern buoy.



### **Cargoes of Particular Hazard**

Vessels carrying a Cargo of Particular Hazard as listed in 33 CFR 126.10 may occupy this anchorage with permission from the Captain of the Port. These vessels may be required to use a stern buoy.

### **Length of Vessel Stay**

Vessels normally remain at this anchorage for no more than seven days. After seven days vessels may be contacted by the USCG for status.

### **Special Considerations**

Additional considerations specific to the Hayden Island Anchorage include:

- There are four water leases along the north shore of Hayden Island (numbered 1 through 4 on the enclosed Chart). The water leases are privately controlled tug and barge marshaling areas. Each marshaling area covers approximately five-acres. Frequently, rafted barges are moored in these areas and tug and barge activity can be heavy, especially late at night or in the early morning hours and shall be considered while anchoring and during the vessels stay at the anchorage.
- Limited space available in this anchorage and the size of the vessels that typically anchor here, care must be taken to avoid crowding.
- The effects of changes in wind, current, and water level, both upon the anchoring vessel and upon other nearby vessels, and barges.
- During seasonal periods of low water levels (usually between September and November) anchoring vessels must remain aware of their under keel clearance while at anchor and of the possibility of going aground.
- Vessel anchoring at the lower buoy must attach to the stern buoy due to the proximity of barges moored at water lease #1.
- Vessels anchored at the Power Lines are in proximity to barges moored at water lease #2 and #3.

### **Emergency Situations**

Tugs are normally available on short notice and can be notified on channels 16, 13 or by contacting the vessel agent.



## **D. Offshore Anchoring**

### **1. Caution**

The practice of anchoring offshore should only be considered in an emergency situation. Should such emergency arise, vessel Masters are cautioned to carefully consider:

- The inherent dangers of anchoring on a lee shore.
- Relevant anchoring exclusion zones.
- Prevailing and forecast weather.
- Currents and tides.
- Traffic.
- The anchor holding characteristics of the anticipated anchor location and their ground tackle.
- The requirements of their vessel for adequate maneuvering (sea) room, considering the time it takes to provide propulsion, heave anchor, their vessel's handling characteristics and the area, wind, currents, tides, sea state, weather and visibility.

### **2. Emergency Offshore Anchoring Requirements**

In general, vessel Masters should always consider standing offshore in preference to anchoring offshore.

- Any vessels requiring an offshore anchorage must immediately notify Coast Guard Sector Portland, the Bar Pilots and their agent.
- The vessel Master shall be prepared to give the nature of the vessels' distress, desired anchor position, depth of water, bottom type, and number of anchors and shots of chain to be used.
- The vessel will be required to maintain a full Bridge Navigation Watch and Engines on Standby, ready for immediate maneuvering.
- The vessel will be placed on a communications schedule with the Coast Guard and will be required to get underway as soon as safely possible.